

FW-3000

Specifications & Features

Dimension: 20" Width \times 16" Length \times 51" Height Shipping weight: 75 lbs

Cold tank volume: 1 gallon Hot tank volume: 0.5 gallon

Cooling rate: 1.5 gal/hour 37-50°F Heating rate: 1.3 gal/hour 180°F

LG Compressor Elegant & modern design Leak detector Hot, cold, & room temperature water Sparkling/soda water option available Hot water safety lock Two hidden built-in cup holders Easy to use control Panel

Antimicrobial coating available UV disinfection and Ozone sterilization systems available Surgical grade stainless steel hot, cold, & room temperature tanks

Filtration Options

3-Stage Carbon Filtration:

- Stage 1: Sediment Filter (5 micron)
- > Stage 2: Activated Carbon Filter (1 micron)
- > Stage 3: Post Carbon Filter (0.5 micron)

Reverse Osmosis Purification:

- > Stage 1: Sediment Filter (5 micron)
- > Stage 2: Activated Carbon Filter (1 micron)
- Stage 3: Reverse Osmosis Membrane*
- Stage 4: Post Carbon Filter (0.5 micron)
 *Available in 50 & 180 GPD







FilterWater.com Tel: 1-800-439-0263 Fax: 1-215-354-0304 www.FilterWater.com Sales@FilterWater.com