ITSsensafe 🛗 ITSsensafe

(800) 831-97/12 **EXACIDIP@SENSAFECOM**

INDUSTRIAL TEST SYSTEMS, INC.

CHLORINE DIOXIDE TEST

Tap **'SELECT** Test' at the top. Tap Chorine Dioxide (DPD-1) Cd. The iDip and app will both display Chlorine Dioxide.



Remove one eXact® Strip Micro Glycine, 484014 and set in a dry, convenient place.



Rinse the cell 3 times with the water sample to be tested and **FILL** to the top to begin test.



Press READ to initiate a 20 second countdown and simultaneously **DIP** the test strip by submerging all pads in the sample then use a gentle constant back and forth motion (2 strokes per second) until the timer displays "1". Remove and discard the strip



App will show that it is ready to continue with the next part of testing. Tap OK. Press (PRO/OI) and the iDip® display reads OPPM indicating the meter is ready to test.



Remove one eXact® Strip Micro Cd, 486633



Press (READ) to initiate a 20 second countdown and simultaneously **DIP** the test strip by submerging all pads in the sample then use a gentle constant back and forth motion (2 strokes per second) until the timer displays "1". Remove and discard the strip.



READ result displayed on the iDip® and in the app. To save your results and make available for emailing, continue on page 11 of your manual. After testing is complete, rinse CELL immediately.



11

12