



A sleek, industry leading reliability, minimal foot print tower unit at an amazing price point; the H2O-400 is perfect for low to mid traffic applications in commercial and residential settings.

The H2O-400 dispenses both hot and cold water, and is equipped with an LG compressor, surgical stainless steel hot and cold tanks. It is available in Shell, Reverse Osmosis, and Ultra Filtration.

SPECIFICATIONS & FEATURES

Dimensions | 11" W x 14.75" L x 43.75" H
 Weight | 46 lbs
 Cold Tank | 1 gallon
 Hot Tank | 0.5 gallon
 Cooling Rate | 1.5 gal/hour 37-50°F
 Heating Rate | 1.3 gal/hour 180°F

LG Compressor
 Anti-Microbial Panels
 Hot & Cold Water
 Hot Water Safety Lock

Hot Power Consumption 1000W
 Cold Power Consumption 100W
 110V~127V AC / 50-60Hz
 Refrigerant R134A
 Climate Class T
USA Final Assembly & Quality Control

2-Stage Filtration

Stage 1: Sediment
 Stage 2: Post Carbon Filter

3-Stage Filtration

Stage 1: Sediment
 Stage 2: Pre-Carbon
 Stage 3: Post Carbon Filter

4-Stage UltraFiltration

Stage 1: Sediment
 Stage 2: Pre-Carbon
 Stage 3: Ultra-Filtration Membrane
 Stage 4: Post Carbon Filter

Reverse Osmosis Purification

Stage 1: Sediment Filter
 Stage 2: Activated Carbon Filter
 Stage 3: 100 GDP Reverse Osmosis Membrane
 Stage 4: Post Carbon Filter

AVAILABLE IN:



white black